



Glass award



Wooden blocks



Package



Wedding welcome sign board



Metal key chain



Customized toy car



Smartphone case



Personalized stationery



Plastic business card/ID card



Metal directory and floor plan

Direct printing on a wide range of materials including plastic, acrylic and metal
UJF-3042MkII and UJF-6042MkII expand creative possibilities

Specifications

		UJF-3042MkII	UJF-6042MkII
Printhead		On-demand piezo printhead (3 printheads arranged in a staggered line)	On-demand piezo printhead (4 printheads arranged in a staggered line)
Print resolution		Maximum: 1200 x 1200 dpi	
Maximum printable area		Width: 300 mm Length: 420 mm (A3 size)	Width: 610 mm Length: 420 mm (A2 size)
Ink	Type/Color	LH-100 (C,M,Y,K,W,C) LUS-120 (C,M,Y,K,W,C) LUS-150 (C,M,Y,K,W) PR-200 (Primer)	LH-100 (C,M,Y,K,Lc,Lm,W,C) LUS-120 (C,M,Y,K,Lc,Lm,W,C) LUS-150 (C,M,Y,K,Lc,Lm,W) PR-200 (Primer)
	Packaging	250 ml bottle / 1 L bottle	
Media	Thickness	153 mm (6 inch) or less	
	Weight	5 kg (11 lb) or less	8 kg (17.7 lb) or less
Certifications		VCCI class A / FCC class A / ETL UL 60950-1 / CB / CE Marking (EMC, Low voltage, Machinery directive, and RoHS) / REACH / Energy Star / IEC60825-1	
Interface		Ethernet / USB2.0	
Noise level		Standby mode: 55 dB or less (FAST-A, measured 1 m away from the source at front, back, right and left sides.) Continuous operation: 65 dB or less Discontinuous operation: 70 dB or less	
Power supply		Single-phase AC100-240V, ±10%, 50/60Hz ±1Hz	
Power consumption		1000 W or less	
Operational environment	Temperature	20 - 30 degC (68 - 86 degF)	
	Humidity	35 - 65 %Rh	
	Recommended Temperature	20 - 25 degC (68 - 77 degF)	
	Acceptable range of temperature change	±10 degC (±50 degF)/h or less	
Dust level		Equivalent to a general office floor level	
RIP software		RasterLink6 (Bundled)	
Dimensions (W×D×H) *1		1,355 mm x 1,290 mm x 856 mm (53.4 in x 50.8 in x 33.7 in)	1,665 mm x 1,290 mm x 856 mm (65.6 in x 50.8 in x 33.7 in)
Weight		135 kg (297.6 lb)	150 kg (330.7 lb)

*1: Heights of ink bottles are not included.

Option

Item	Item No.	Note
UJF-3042/6042MkII		
Installation stand	OPT-J0420	
Ventilating fan unit	OPT-J0424	
UJF-3042MkII		
Ionizer unit 30	OPT-J0414	
Vacuum table 30	OPT-J0421	
Status indication lamp unit	OPT-J0423	Indicating lamp (QTY:1) Emergency stop switches (QTY:2)
NCU option	OPT-J0422	
UJF-6042MkII		
Ionizer unit 60	OPT-J0415	

Please note that descriptions and data in this brochure are as of September 1st, 2016 and subject to change.

User friendly RIP "RasterLink6" as a standard feature

RasterLink6

- ◆ More beautiful and advanced print results are achieved by following a user-friendly interface that is easy to operate.
- ◆ Color replacement function enhances the ability to re-create printed images.
- ◆ Print color can be simulated on Illustrator / Photoshop without an actual print.
- ◆ This function requires MPM2 (Mimaki Profile Master 2).
- ◆ Supports Web update function
- ◆ Program update and profile download can be easily performed via internet.

● All trademarks or registered trademarks are the property of their respective owners. ● Descriptions and data in this brochure are subject to change without notice. ● Some of sample images in this brochure are simulated. ● The printhead ejects extremely fine dots for printing, and therefore printed colors may vary after replacing the printheads. ● When using multiple printer units, printed colors would be different slightly because there is a slight difference among those units.


Mimaki MIMAKI ENGINEERING CO., LTD.
2182-3 Shigeno-otsu, Tomi-city, Nagano 389-0512, Japan
Tel: +81-268-78-2288 trading@mimaki.jp

Mimaki Global Network

USA	MIMAKI USA, INC.	Europe	MIMAKI EUROPE B.V.
Brazil	MIMAKI BRASIL COMERCIO E IMPORTACAO LTDA	Indonesia	PT. MIMAKI INDONESIA
India	MIMAKI INDIA PRIVATE LIMITED	Australia	MIMAKI AUSTRALIA PTY. LTD.
Taiwan	MIMAKI ENGINEERING (TAIWAN) CO.,LTD.	China	SHANGHAI MIMAKI TRADING CO.,LTD.
Singapore	MIMAKI SINGAPORE PTE. LTD.		

Supplies

Item	Item No.	Note
Cyan	LUS12-C-BA	1L bottle
Magenta	LUS12-M-BA	
Yellow	LUS12-Y-BA	
Black	LUS12-K-BA	
Light cyan	LUS12-LC-BA	
Light magenta	LUS12-LM-BA	250ml bottle
White	LUS12-W-BA	
Clear	LUS12-CL-BA	
Cyan	LUS12-C-B2	
Magenta	LUS12-M-B2	
Yellow	LUS12-Y-B2	1L bottle
Black	LUS12-K-B2	
Light cyan	LUS12-LC-B2	
Light magenta	LUS12-LM-B2	
White	LUS12-W-B2	
Clear	LUS12-CL-B2	250ml bottle
Cyan	LUS15-C-BA	
Magenta	LUS15-M-BA	
Yellow	LUS15-Y-BA	
Black	LUS15-K-BA	
Light cyan	LH100-LC-BA	1L bottle
Light magenta	LH100-LM-BA	
White	LH100-W-BA	
Clear	LH100-CL-BA	
Cyan	LH100-C-B2	
Magenta	LH100-M-B2	250ml bottle
Yellow	LH100-Y-B2	
Black	LH100-K-B2	
Light cyan	LH100-LC-B2	
Light magenta	LH100-LM-B2	
White	LH100-W-B2	1L bottle
Clear	LH100-CL-B2	
UJ Primer PR-200	PR200-Z-B	250ml bottle
	PR200-Z-B2	1L bottle
Flushing liquid 07	FL007-Z-BA	1L bottle



Flatbed UV-LED Inkjet Printer


UJF-3042 MkII
UJF-6042 MkII



Creating More Value



Creating More Value



Direct printing on objects up to A3 or A2 size and 153 mm thick

The best-in-class productivity delivers effective on-demand print production

The UJF-3042MkII and the UJF-6042MkII models achieve a maximum print speed of 2.48 m²/h (*1) and 3.52 m²/h (*2). The best-in-class productivity exhibits an approximately 20% (*3) faster print speed than that of conventional models and support on-demand print production. Staggered printhead arrangement allows printing process and spot colors simultaneously.*4)

*1: 38 A4 size images per hour / Print conditions: 4-color, draft mode, 600 x 600 dpi, 8Pass
 *2: 52 A4 size images per hour / Print conditions: 6-color, draft mode, 600 x 600 dpi, 8Pass
 *3: When printing is performed with the standard mode.
 *4: Dependent on the ink-setting; simultaneous printing might not be possible in every case.
 A4 size: 210 x 297 mm (8.27 x 11.7 in)

Approximately **20%** faster print speed than conventional models

1. Process color printing					1. Process color printing				
Print mode	Resolutions	Pass	Print speed (m ² /h)	Printing time per A3 size	Print mode	Resolutions	Pass	Print speed (m ² /h)	Printing time per A2 size
Draft	600x600	8	2.48	3min. 03sec.	Draft	600x600	8	3.52	4min. 22sec.
High-speed	600x900	12	1.62	4min. 40sec.	High-speed	600x900	12	2.29	6min. 42sec.
Standard	600x1200	16	1.22	6min. 51sec.	Standard	600x1200	16	1.74	8min. 51sec.
High-quality	1200x1200	16	0.89	8min. 27sec.	High-quality	1200x1200	16	1.28	11min. 59sec.

2. Color + Spot color simultaneous printing					2. Color + Spot color simultaneous printing				
Print mode	Resolutions	Pass	Print speed (m ² /h)	Printing time per A3 size	Print mode	Resolutions	Pass	Print speed (m ² /h)	Printing time per A2 size
Draft	600x600	8	2.08	3min. 38sec.	Draft	600x600	8	2.99	5min. 08sec.
High-speed	600x900	12	1.44	5min. 14sec.	High-speed	600x900	12	2.06	7min. 28sec.
Standard	600x1200	16	1.12	6min. 46sec.	Standard	600x1200	16	1.57	9min. 46sec.
High-quality	1200x1200	16	0.69	10min. 55sec.	High-quality	1200x1200	16	0.96	15min. 57sec.


3. Color + White simultaneous printing with the high-dense mode					3. Color + White simultaneous printing with the high-dense mode				
Print mode	Resolutions	Pass	Print speed (m ² /h)	Printing time per A3 size	Print mode	Resolutions	Pass	Print speed (m ² /h)	Printing time per A2 size
Draft	600x600	8	1.88	4min. 01sec.	Draft	600x600	8	2.75	5min. 36sec.
High-speed	600x900	12	1.33	5min. 40sec.	High-speed	600x900	12	1.86	8min. 11sec.
Standard	600x1200	16	1.03	7min. 21sec.	Standard	600x1200	16	1.44	10min. 36sec.
High-quality	1200x1200	16	0.62	12min. 14sec.	High-quality	1200x1200	16	0.85	18min. 09sec.

A3 size: 297 mm x 420 mm (11.69 in x 16.54 in)

A2 size: 420 mm x 594 mm (16.54 in x 23.39 in)

Staggered printhead arrangement allows printing process and spot colors simultaneously*

636 nozzles per printhead (318 nozzles per each nozzle line)



* Illustration of process and spot color printing

* Dependent on the ink-setting; simultaneous printing might not be possible in every case.

High-performance UV-curable inks expand the range of applications

Flexible LUS-120 ink can print on soft materials such as leather or TPU

The flexible LUS-120 ink stretches up to 170% and delivers beautiful and durable print results on soft materials including leather or polyurethane. Ideal applications of the LUS-120 ink are membrane switches or wallet smartphone cases that must be pressed or folded.



Flexible LUS-150 ink has excellent adhesion to acrylic


The LUS-150 ink stretches up to 150% and delivers vibrant color representation. In addition to its use on soft materials, this ink adheres very well to rigid materials such as glass or acrylic. Examples of ideal applications are indoor signs or trophies.




* This LUS-150 ink will be loadable in the future.

Rigid LH-100 ink features high scratch-resistant. Ideal for decorative printing on small items

The LH-100 ink features high scratch-resistant, and has excellent color reproducibility. Ideal applications are smartphone cases, key fobs and toys.



The clear ink offers valuable new print effects



Mimaki clear control (MCC) has been newly added to the UJF-3042/6042MkII models. In order to minimize dust adhesion and air bubbles on the print, MCC shortens the ink curing time by processing the clear ink print and UV-light irradiation simultaneously. MCC provides a gorgeous gloss finish.


Various print effects with the clear ink



Mimaki's unique techniques provides more beautiful print


Mimaki Expand Color improves color representation

The new input profile, Mimaki Expand Color, is added to Mimaki genuine RIP software, RasterLink6. This profile enables representing more vibrant solid colors and brighter skin tones than a conventional input profile and provide more attractive print results with high-contrast color shades; bright parts are brighter and dark parts are darker.



Waveform control and variable dot printing achieve smooth and quality print image


Each ink color has its own specific gravity and viscosity. To achieve a precise placement of ink droplets onto the media, Mimaki has designed an optimum waveform control technique that allows the printhead to jet each ink color at an optimum angle, maintaining excellent ink droplet circularity. Thanks to precise ink droplet landing, three different droplet sizes (5 pl to 22 pl *) are properly used for providing optimum print results.



* The maximum droplet size is 27 pl when using white high-dense mode.

Mimaki Advanced pass System 4 (MAPS4) minimizes banding and uneven color printing

Generally, swath boundaries are straight lines. Therefore, a slight misalignment between boundaries causes banding or uneven color printing. MAPS4 reduces banding and uneven color printing with blurred boundaries similar to gradation printing according to print conditions including media/ink type and resolutions.



Ink supply unit
Bottled inks can be set in the unit. This feature reduces operational cost.

Advanced mechanical structure assists value-added print products

Fully covered print table
The fully covered print table improves the safeness of the printer. It also maintains print quality by reducing dust adhesion.

Operation panel
3.45-inch (52.56 x 70.08 mm) color liquid crystal display provides useful information and allows easy setting and operation.

Table-driven printing
To achieve higher positional accuracy, the vibration of the printer unit is reduced by using table-driven printing.

Printable thickness is up to 153 mm
Direct printing on objects of up to 153 mm in thickness.

Nozzle trouble avoidance features

- Nozzle Check Unit (NCU)** automatically detects and recovers clogged nozzles(*1)
- Nozzle Recover System (NRS)** for maintaining productivity(*2)
- Mimaki Circulation Technology (MCT)**

The flowchart shows the process: Start printing process -> NCU (Nozzle failure) -> Cleaning -> NCU (Nozzle failure) -> NRS -> Continue printing.

*1: NCU is a standard feature of UJF-6042MkII, and an optional feature of UJF-3042MkII. *2: NRS may not be activated depending on print modes. *3: MCT works only with white ink.